



C A R D P R I N T E R S

The printer of choice for entry-level users.

When your needs call for an entry-level card printer that's portable, easy-to-use and affordable, the FARGO Quatro or FARGO Uno are smart solutions.

For color applications, choose the FARGO Quatro. Its advanced dye-sublimation technology and 32-bit print spooler work together to produce brilliant, full-color cards in just 40 seconds. Plus, it prints edge-to-edge for more professional-looking cards and is available with FargoColor™ color matching software for precise color reproduction.

Just need monochrome printing? FARGO Uno is for you. It prints 256 shades of gray for producing crisp, clear single-color photos, text and bar codes. It even offers a variety of resin ribbon colors for printing in red, blue, green, metallic gold and more. Plus, the Uno prints a card in just 5 seconds – the fastest speed in its class!

Both models are available with optional magnetic stripe encoding for enhanced security, and come standard with convenient drop-in ribbon loading and an operator-replaceable printhead.

If you are looking for a compact, entry-level card printer with truly impressive features, look no further than FARGO!



STANDARD
CARDS



EDGE-TO-EDGE



MAG STRIPE



COLOR
MATCHING

Quatro Uno

FARGO®



Quatro/Uno Card Printer Specifications

Print Method:	Quatro: Dye-Sublimation/Resin Thermal Transfer Uno: Resin Thermal Transfer
Resolution:	300 dpi (11.8 dots/mm)
Colors:	Quatro: Up to 16.7 million Uno: Monochrome
Print Speed:	Quatro: Approximately 40 seconds (Y,M,C,K,O)* Uno: Approximately 2.5 seconds (print time) (K)* Approximately 5 seconds (total throughput) (K)
	*Indicates the ribbon type and the number of ribbon panels being printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, B=Dye-Sub Black and O=Overlay
Maximum Print Width:	Quatro: 2.13" (54mm); edge-to-edge printing is available on standard CR-80, .030" (.76mm) cards only. Uno: 2.02" (51mm)
Maximum Print Length:	Quatro: 3.38" (86mm) Uno: 3.31" (84mm)
Accepted Card Width:	2.1" x 2.13" (53mm x 54mm)
Accepted Card Length:	3.25" to 3.37" (82mm to 86mm)
Accepted Card Thickness:	.020" to .040" (.5mm to 1.0mm); also accepts most .010" (.254mm) cards
Card Types:	PVC or polyester cards with polished PVC finish; monochrome resin ribbon required for straight polyester cards
Card Capacity:	150 PVC cards (.010"), 50 PVC cards (.030")
Software Drivers:	Windows® 3.1x, Windows 95/98, Windows NT (Quatro only) and Macintosh® (Quatro only); 32-bit print spooler for Windows 95/98
Interface:	Standard 8-bit Centronics-type parallel (ECP-compatible)
Operating Temperature:	65° to 80° F (18° to 27° C)
Humidity:	20-60% non-condensing
Dimensions:	5.88"H x 12.19"W x 10.27"D (149mmH x 310mmW x 261mmD)
Weight:	15 lbs. (7kg)
Agency Listings:	Safety: UL 1950, CSA C2.2 and TÜV-GS (IEC-950) Emissions: FCC Class A, CRC c1374, Class A and TÜV-EMC (IEC-801 -2, -3, -4; CISPR 22, Class B), CE
Supply Voltage:	100/110/220 VAC
Supply Frequency:	50 Hz/60 Hz
Warranty:	Printer – One year; optional Extended Warranty Program (U.S. only) Printhead – One year or 50,000-pass usage-allowance with UltraCard cards (whichever comes first)
Options:	<ul style="list-style-type: none"> • ISO Magnetic Stripe Encoding Module, high- or low-coercivity (specify when ordering), Tracks 1, 2, and 3 • JIS II Magnetic Stripe Encoding Module • FargoColor Color Matching Software • Printer Cleaning Kit

FARGO®

6533 Flying Cloud Drive
Eden Prairie, MN 55344 USA
(612) 941-9470
800-459-5636
Fax: (612) 941-7836
www.fargo.com
E-mail: sales@fargo.com

This data sheet is for informational purposes only. FARGO Electronics makes no warranties, expressed or implied, in this summary. Company and product names and data used in sample output are fictitious. Specifications are subject to change without notice. FARGO is a registered trademark of FARGO Electronics, Incorporated. All other trademarks and registered trademarks are property of their respective companies. This is not an offer of sale.

© 1998, FARGO Electronics, Incorporated. All rights reserved. SL1036-REV9809